

CHRISTIE GRIFFYN 4K50-RGB

Large-scale events and venues | Rental and staging
Projection mapping | Sports venues | Theme parks and attractions

Pure laser. Pure performance. Pure excellence.

A technological marvel, the Christie Griffyn® 4K50-RGB™ pure laser projector combines superior Christie electronics, our proprietary RGB laser illumination architecture with integrated cooling, and a sealed optical path for reliable illumination performance and capabilities that will impress you.

Ready to illuminate any surface with 50,000 lumens while operating at 55dBA at full brightness, the highly advanced Griffyn 4K50-RGB is designed for demanding large-venue applications on the ground or in the air.

Design excellence

This powerful all-in-one, omnidirectional projector offers our TruLife+™ electronics platform with all-in connectivity, eliminating the hassle of removable option cards because everything you need is built in. Griffyn also includes our new electronic color convergence (ECC), which allows you to adjust convergence via remote control for easy, picture-perfect color alignment. The Griffyn 4K50-RGB once again raises the bar in RGB pure laser projection performance.

We thought of everything

- › All-in-one, compact design – No external chillers or lasers and a manageable weight of 197lbs makes it the smallest, lightest brightest 3DLP® RGB laser projector available.¹
- › Expanded color gamut – Produces ~98% of the Rec. 2020 color space for rich, vibrant and true-to-life visuals.
- › Christie TruLife+ electronics – every connection you need is built-in, at no extra cost.
- › Electronic color convergence (ECC) – Easily adjust convergence via remote control for picture-perfect color alignment.
- › Christie Twist™ – Built-in image warping and multi-projector blending software.
- › Christie Mystique™ – automated camera-based alignment software, quickly install, align, and calibrate and maintain multi-projection systems in minutes.
- › 4K lens compatibility – Compatible with all Christie 3DLP® ILS4 4K lenses



CHRISTIE®

Technical specifications

Christie Griffyn 4K50-RGB

Image	brightness	<ul style="list-style-type: none"> • 50,000 ISO lumens • 44,500 ANSI lumens^{2,3,4} 	
	contrast	<ul style="list-style-type: none"> • 5000:1 On/Off with high-contrast lens 	
Display technology	type	<ul style="list-style-type: none"> • Dust-sealed 3DLP® (1.38") 	
	resolution	<ul style="list-style-type: none"> • 4096 x 2160 (4K) 	
Sound		<ul style="list-style-type: none"> • 46dBA/55dBA^{5,6} 	
Illumination	type	<ul style="list-style-type: none"> • Solid-state RGB (red, green & blue) pure laser 	
	performance	<ul style="list-style-type: none"> • Over 50,000 hours in standard mode 	
	color performance	<ul style="list-style-type: none"> • ~98% coverage of Rec. 2020 	
	field replaceable	<ul style="list-style-type: none"> • Yes 	
Orientation		<ul style="list-style-type: none"> • Omnidirectional 	
Image processing		<ul style="list-style-type: none"> • Christie TruLife+™ electronics, 1.2Gpx/s 	
Frame rates	standard	<ul style="list-style-type: none"> • 24-60Hz 	
	optional	<ul style="list-style-type: none"> • Christie Mirage option: 4K@120Hz and 4K 3D@60Hz per eye • Christie Mirage Pro option: all the features of the Mirage option plus 2K@240-480Hz and Christie View simultaneous multi-content viewer 	
Inputs	standard	<ul style="list-style-type: none"> • 4 x 12G-SDI • 2 x HDMI 2.0 • 2 x DisplayPort 1.2 • HDBaseT • Audio out • Fiber (QSFP+) for use with Christie Link Transmitter (1 input/1 output) 	
Warping and blending	standard	<ul style="list-style-type: none"> • Christie Twist™ • Christie Mystique™ Lite can be downloaded at no extra charge 	
	optional	<ul style="list-style-type: none"> • Christie Twist Premium and Twist Pro • Christie Mystique • Christie Guardian 	
Multi-projector management	optional	<ul style="list-style-type: none"> • Christie Conductor - monitors/controls up to 256 projectors on a single network and can be downloaded at no extra charge 	
Lenses	high brightness	<ul style="list-style-type: none"> • 0.38:1 UST high brightness (ILS4) • 0.72:1 high brightness (ILS4) • 0.9:1 high brightness (ILS4) • 1.13-1.66:1 high brightness (ILS4) • 1.45-2.17:1 high brightness (ILS4) 	<ul style="list-style-type: none"> • 1.95-3.26:1 high brightness (ILS4)⁷ • 2.71-3.89:1 high brightness (ILS4)⁷ • 3.89-5.43:1 high brightness (ILS4)⁷ • 4.98-7.69:1 high brightness (ILS4)⁷
	ultra high contrast ³	<ul style="list-style-type: none"> • 0.72:1 ultra high contrast (ILS4) • 0.9:1 ultra high contrast (ILS4) • 1.13-1.66:1 ultra high contrast (ILS4) • 1.45-2.17:1 ultra high contrast (ILS4) 	<ul style="list-style-type: none"> • 1.95-3.26:1 ultra high contrast (ILS4)⁷ • 2.71-3.89:1 ultra high contrast (ILS4)⁷ • 3.89-5.43:1 ultra high contrast (ILS4)⁷
Power	line voltage	<ul style="list-style-type: none"> • 200-240 VAC, 19A, 50/60Hz Single phase • Connector: IEC60309 30A 	
	power consumption	<ul style="list-style-type: none"> • 2800W typical (9,550 BTU/hr) • 3800W max (13,000 BTU/hr) 	
Cooling		<ul style="list-style-type: none"> • Liquid, self-contained 	
Laser class		<ul style="list-style-type: none"> • Class 1 – Risk Group 3 	
Operating environment		<ul style="list-style-type: none"> • 5-40°C (41-104°F) • Relative humidity: 10-80% non-condensing 	
Dimensions	size	<ul style="list-style-type: none"> • (LxWxH): 36.3 x 25 x 15" (922 x 635 x 380mm)⁸ 	
	weight	<ul style="list-style-type: none"> • 197lbs (89.3 kg)⁸ 	

¹ At time of release - May 2022

² D65 white measured at 23°C (73.4°F)

³ Brightness is reduced up to 30% with the use of a high-contrast lens

⁴ In ambient temperatures up to 30°C

⁵ 46dBA in quiet fan mode at 23°C, 55dBA in standard fan mode at 23°C

⁶ Sound pressure measurement, measuring conditions, and method of notation all comply with ISO7779-1999. Sound level may vary between units

⁷ Requires lens hood extension for Class 1, Risk Group 3

⁸ Without lens

For the most current specification information, please visit christiedigital.com

Copyright 2022 Christie Digital Systems USA, Inc. All rights reserved. All brand names and product names are trademarks, registered trademarks or tradenames of their respective holders. "Christie" is a trademark of Christie Digital Systems USA, Inc., registered in the United States of America and certain other countries. DLP® and the DLP logo are registered trademarks of Texas Instruments. Performance specifications are typical. Due to constant research, specifications are subject to change without notice.
CD3113-Griffyn-4K50-datasheet-Nov-22-EN



CHRISTIE®